

CLAIMS

WHAT IS CLAIMED IS:

1. A media wrapper for use in a printing device comprising:
a first end;
a second end; and
a perforation disposed between said first and second ends;
wherein said perforation is configured to split said media wrapper to separate said first and second ends.
2. The media wrapper of claim 1, wherein said perforation is disposed between said first and second ends such that when said media wrapper is split, a first end is removed to expose a contained print media.
3. The media wrapper of claim 2, further comprising:
a pull tab;
wherein said pull-tab is configured to split said perforation.
4. The media wrapper of claim 3, wherein said pull-tab comprises a plastic ribbon disposed within said media wrapper.
5. The media wrapper of claim 3, wherein said pull tab comprises an extruded portion of said media wrapper.
6. The media wrapper of claim 3, further comprising:
a placement indicator;
wherein said placement indicator is configured to indicate a nap of said print media.

7. The media wrapper of claim 6, wherein said placement indicator comprises a seam.

8. The media wrapper of claim 6, wherein said placement indicator comprises a label.

9. A ream of print media comprising:
print media; and
a print media wrapper including a first end, a second end, and a perforation disposed between said first and second ends, wherein said perforation is configured to split said media wrapper to separate said first and second ends.

10. The ream of print media of claim 9, wherein said perforation is disposed between said first and second ends such that when said print media wrapper is split, a first end is removed to expose said print media.

11. The ream of print media of claim 10, further comprising:
a pull tab;
wherein said pull-tab is configured to split said perforation.

12. The ream of print media of claim 11, wherein said print media wrapper further comprises a placement indicator;
said placement indicator being configured to indicate a preferred nap side of said print media.

13. A method of removing a packaging wrapper from a media used in a document producing device comprising;
sectioning said packaging wrapper;
detaching a section of said packaging wrapper; and
exposing a portion of said media.

14. The method of claim 13, wherein said packaging wrapper comprises a perforated strip.

15. The method of claim 14, wherein the said packaging wrapper is separated by a detaching device configured to split said perforated strip.

16. The method of claim 15, wherein said detaching device comprises a pull tab.

17. The method of claim 16, wherein said pull tab comprises a plastic ribbon disposed on said packaging wrapper

18. The method of claim 13, wherein said media comprises paper.

19. The method of claim 13, wherein said media comprises transparencies.

20. The method in claim 13, wherein said wrapper further comprises a placement indicator;

said placement indicator being configured to indicate a preferred nap side of said print media.

21. A printing apparatus comprising:

an image printing mechanism;

a take up roller configured to feed print media to said image printing mechanism; and

a feed tray;

wherein said take up roller is further configured to access a ream of print media on said feed tray, said ream of print media being contained by a portion of a print media wrapper.

22. The printing apparatus of claim 21, wherein said image printing mechanism comprises a laser printer.

23. The printing apparatus of claim 21, wherein said image printing mechanism comprises an ink-jet printer.

24. The printing apparatus of claim 21, wherein said image printing mechanism comprises a copy machine.

25. The printing apparatus of claim 21, wherein said image printing mechanism comprises a facsimile machine.

26. The printing apparatus of claim 21, wherein said feed tray is configured to receive multiple reams of print media being contained by a portion of a print media wrapper.

27. A media packaging wrapper for a media used in a document producing device comprising;
a wrapping means for wrapping print media; and
a separating means for separating said wrapping means.

28. The media packaging wrapper of claim 27, further comprising splitting means for splitting said separating means.

29. The media packaging wrapper of claim 27, wherein said separating means comprises a perforated strip.

30. The media packaging wrapper of claim 27, wherein said separating means comprises a pull-tab.

31. The media packaging wrapper of claim 30, wherein said pull-tab comprises a plastic ribbon disposed within said wrapping means.

32. The media wrapper of claim 30, wherein said pull tab comprises an extruded portion of said wrapping means.

33. The media wrapper of claim 27, further comprising indicating means for indicating a desired orientation of a nap of said media.

34. The media wrapper of claim 33, wherein said indicating means comprises a seam of said wrapping means.

35. The media wrapper of claim 33, wherein said indicating means comprises a label.

36. A method of supplying print media to a printing device comprising:
separating a print media wrapper into multiple pieces;
removing a piece of said print media wrapper, wherein said removal exposes a portion of said print media; and
providing said exposed portion of said print media to a pick-up roller of said printing device.

37. The method of claim 36, further comprising leaving a portion of said print media wrapper coupled to said print media;
said portion of said print media wrapper being configured to provide organizational support to said print media.

38. The method of claim 37, wherein said portion of said print media wrapper comprises an information label.

39. The method of claim 36, wherein said separating a print media wrapper comprises:

pulling a tab; and

separating said print media wrapper along a perforated seam.

40. The method of claim 39, wherein said tab comprises an extruded portion of said media wrapper.

41. The method of claim 36, wherein said providing said exposed portion of said print media to a pick-up roller comprises:

disposing said print media, including a portion of said print media wrapper, on a tray or cassette; and

coupling said tray or cassette to said printing device.

42. The method of claim 41, wherein said disposing said print media further comprises disposing multiple reams of print media, including a portion of said print media wrapper, on a tray or cassette.